

Semi-Style **Sprayer Trailer** 45,000 GVW



Trailers shown with 20" outriggers



Optional beavertail



Semi-style sprayer trailer with tank mounted

Standard Features

Main Frame	16" I Beam, 26 lbs. Per Foot
Capacity	45,000 lb. GVWR; Split or Non-split Axles
Outriggers	16" Flip-up Style
Axles	(2) 22,500 lb. Oil Bath Heavy Duty Axle with Automatic Slack Adjusters and Park Brake (one axle ABS equipped)
Wheel	(8) 22.5" x 8.25" Hub Piloted Wheels, 10 on 11.25" Bolt Pattern
Tires	(8) 255/70R-22.5 Tire
Lighting	DOT Approved, All Sealed Rubber Mounted LED
Hitch	King Pin, 48" Ground Clearance, 2" SAE with 3/8" Bolster Plate
Jack	(2) Dual Speed Holland Landing Gear
	Reflector Tape
	Mud Flaps
Finish	Bead Blasted, Acid Washed, Electrostatic Powder Coated

Optional Features

Heavy Duty Fenders (if no deck)	Steel Decking (frame width 39")
Spare Tire and Wheel	Steel Decking (full width 92")
Upper Wood Deck (96")	Mesh Decking (full width 39")
Lower Wood Deck (92")	Beavertail
Extra Length	3rd Axle
20" Outriggers	



BEHNKE ENTERPRISES, INC.
800 Ninth Ave. NW. | Farley, Iowa 52046
Ph. 563-744-3246 | Fax 563-744-9066
www.behnkeenterprises.com

