

SCHULTE®

SMR-600/800 Multi Rake Windrower



The Perfect Tool for your Skid Steer: Windrowing, Landscaping Soil Conditioning and Sweeping



- SMR-600 Shown -

- 1** The rototilling action of the SMR-600 & SMR-800 breaks lumps, roots and other debris while reclaiming rocks by forming them in uniform rows.
- 2** The 4" teeth give you greater ground penetration and are made of wear resistant Hardox 450.
- 3** The SMR-600 & SMR-800 are chain driven to keep the hydraulic motor out of harm's way.
- 4** Option for standard solid mount or floating mount that can pivot up to 20 degrees left or right, manually or hydraulically.
- 5** Solid mounted or hydraulic lifting 23" forklift grade tires for increased maneuvering and rugged durability.
- 6** High or low flow hydraulic options.
- 7** Sweeper options shown on back.

WORLD CLASS - BUILT TO LAST

SMR-600/800 Specifications




- Great for land use preparation -



- Drum angle movement 20 degrees left or right -

SPECIFICATIONS

	SMR-600	SMR-800
Weight (approximate)	1600 lbs (725 kg)	1900 lbs (862 kg)
Hydraulic low flow option	18-24 gpm (68 lpm-90 lpm)	18-24 gpm (68 lpm-90 lpm)
Hydraulic high flow option	28-38 gpm (106 lpm-144 lpm)	28-38 gpm (106 lpm-144 lpm)
Drum width	73" (1.85 m)	89" (2.26 m)
Drum speed	220-250 rpm	220-250 rpm
Tires	23" forklift (58 cm)	23" forklift (58 cm)
Transport width	88" (2.23 m)	102" (2.59 m)




- Ground before Multi Rake use -

- Ground after Multi Rake use -

OPTIONS

Mount options: Standard Mount or Floating Mount,
Joystick control for New Holland, Case, John Deere & Cat
Forklift tires and arms on SMR-800



- Floating Mount -

- Standard Mount Shown -



- Optional broom attachment for sweeping parking lots, roads or removing snow -



Gearbox features reversible tensioner and heavy 80 chain which decreases downtime. The gear ratio has a larger bottom sprocket that increases the mechanical advantage, giving deeper ground penetration and fewer stall outs. Side plates are adjustable, removable, and reversible for varying ground applications.



- 4" teeth made from Hardox 450 -
For superior wear resistance



- Replaceable teeth on the SMR-600 -



- Heavy duty bearings -
Same bearing as used on SRW-1400



Sold By:



ISO 9001

PRINTED IN CANADA

PREPARED by NELSON GRAPHIC DESIGN

2015/0