

Walinga Ultra-Veyor



Your Ultra-Veyor Grows As You Grow

It's always nice to plan ahead and avoid expensive upgrades. The Walinga Ultra-Veyor system is so flexible, easy to install or retro-fit that you can add to your system as your business grows. Choose from an extensive selection of options and specifications to perfectly match your current business demands and keep those hard earned dollars in your pocket.

Move your grain safer & easier, without elevator legs or portable augers.

Walinga Advantage

- Simple installation (DIY)
- Our technicians will communicate with your electrician
- > Gentle on product
- Economic & affordable solution for long distance conveyance

CAPACITY

Capacity in Dry Corn / Deduct 30% if conveying wheat or beans

| MODEL | | 5510 5" TUBING SIZE | | | | 5614 5" TUBING SIZE | | | 6614 6" TUBING SIZE | | | |
|-------------------------------|-----|-------------------------------|------|------|------|-------------------------------|------|------|------------------------|------|------|------|
| MOTOR* | | 15HP | 20HP | 30HP | 40HP | 30HP | 40HP | 50HP | 40HP | 50HP | 60HP | 75HP |
| CONVEYING DISTANCE IN FEET | 100 | 750 | 1000 | 1300 | 1600 | 1250 | 1675 | 1725 | 1800 | 1900 | 2100 | 2300 |
| | 200 | 638 | 850 | 1105 | 1360 | 1063 | 1424 | 1466 | 1530 | 1615 | 1785 | 1955 |
| | 300 | 542 | 723 | 939 | 1156 | 903 | 1210 | 1246 | 1301 | 1373 | 1517 | 1662 |
| | 400 | 461 | 614 | 798 | 983 | 768 | 1029 | 1059 | 1105 | 1167 | 1290 | 1412 |
| | 500 | 392 | 522 | 679 | 835 | 653 | 874 | 900 | 940 | 992 | 1096 | 1201 |

*Single phase option available up to 40 HP



ALL THE WORKING COMPONENTS ON THE GROUND!

The Ultra-Veyor moves bulk product virtually dust and damage free without the use of heavy augers. Maintenance is performed easily at ground level with simple access to all filters, belts and lubrication points.



www.flaman.com