



FX107 ROTARY CUTTER

7 Foot, Single Rotor, Domed Deck Mower

- Rigid single domed, 7 gauge heavy duty deck construction
- ½" x 3" deck protection ring guards against blade to deck damage
- Pull type and 3pt hitching options
- Larger, more durable pan
- 540 RPM drive
- Pull type unit accepts open clevis, solid tongue, adjustable clevis or precision hitch options
- Heavy duty gearbox and driveline, the same units as on our large cutters
- Double safety chains standard front and rear on all units



World Class Built to Last

schulte.ca

FX-107 Specifications

SPECIFICATIONS

Overall Width	84" (2.13m)
Overall Length	95.5" (2.43m)
Transport Clearance	10.5" (26.7cm)
Cutting Height	3" - 13" (7.6cm-33cm)
Cutting Width	109.25" (2.78m)
Cutting Capacity	3" (7.6cm)
Approximate Weight	2010lbs (912kg) trailing, 1980lbs (898kg) 3pt
Hitch Type	Cat. II & III 3pt, Cat. II quick hitch / Trailing pull
Deck Thickness	7ga (3/16", 4.6mm)
Side Skirt	1/4" x 13.69" (6.35mm x 347mm)
Gear Box Rating	210hp (157 kw)
Blade Tip Speed	540rpm-17086fpm
Tractor PTO Speed	540rpm
Minimum Tractor HP	50hp (37.3kw)
Deflectors	Double chain front and rear



FX-107




3pt Unit Shown



Trailing Unit Shown



Heavy Duty Gearbox



Standard Deck Protection Ring



Heavy Duty, Spun Formed
Stump Jumper Pan



2 Piece Replaceable Skid Shoes

OPTIONS - FX-107

- 3pt hitch • Trailing hitch • Standard clevis • Adjustable clevis • Solid tongue • Precision hitch • Laminate tires • Severe Duty tires • Severe duty foam filled tires • Forklift tires



Open Clevis Hitch



Adjustable Clevis



Solid Tongue Hitch



Precision Hitch



ISO 9001

Sold By:

Schulte is a registered trademark of Alamo Group Inc.

Schulte Industries Ltd. reserves the right to change the design and specifications of it's products without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment.

Printed in Canada

Prepared by NELSON GRAPHIC DESIGN

201709

